



Corridor Luminaire Range

					
Key Features	Chamaeleon Deco	Lake Downlight	Chamaeleon III	Chamaeleon Eco	Vico Batten
Government Rebate Schemes Approved for use- lighting upgrades	NSW ESS / IPART Vic VEET		NSW ESS / IPART Vic VEET	NSW ESS / IPART Vic VEET Scheme	NSW ESS / IPART Vic VEET Scheme
High Performance LEDs	SMD 3014	SMD 2835	Lumileds LUXEON 3020	Lumileds LUXEON 3020	Samsung 5630
Integrated controls	Microwave motion sensor		Microwave motion sensor	Microwave motion sensor	Microwave motion sensor
Power Consumption Full light	21-23W	12W, 22W, 32W	Up to 43W	22W -25W	Up to 46W
Power Consumption Standby light	9-10W		4-5W	3-6W	7-12W
Lumen Output Range (lm)	1,800 lumens	1,240 to 3,440 lumens	Up to 3,500 lumens	2,500 lumens	Up to 4,200 lumens
Warranty - Luminaire	5 years	5 years	5 years	5 years	3 years
Emergency Classification	D40		D32/D40	D50	18W, 36W models -D40 44W model -D32
IP Rating	IP65	IP44	IP52, IP65	IP65	IP65
IK Rating	IK10 - Charcoal Black IK09 - Arctic White		IK10	IK10	IK10
Low maintenance features			Smart connect base	Pre-drilled holes, swivel screw gear tray	
smartsense controls -optional	Integrated PE Cell		Smartphone App	IR Remote control	
Mounting	Ceiling or Wall	Ceiling	Ceiling or Wall	Ceiling	Ceiling or Wall
Battery type	Ni-Cd		Ni-MH	Ni-Cd	18W Ni-Cd 36 &44W Ni-MH