





## Warehouse/ Factory: High / Low Bay Product Range

		
Key Features	Tauro Eco	Stargate
Government Rebate Schemes Approved for commercial lighting upgrades	NSW Energy Savings Scheme Vic VEET Scheme	NSW Energy Savings Scheme
High Performance LEDs	Lumiled LUXEON TX	Lumiled LUXEON 3030 2D
Driver Type	Meanwell HLG	Meanwell
Luminaire Efficacy	113 lm/W	130 lm/W
Power Consumption Range(W)	80W, 120W, 160W, 200W, 240W	100W, 150W, 200W
Lumen Output Range (lm)	8,850 - 26,990	13,000 - 26,000
Warranty - Luminaire	5 years	5 years
Ambient Operating Temperature	-40° to +50°C	-30° to +50°C
Colour Temperature (CCT)	5000K standard 4000K & 5700K on request	5700K standard 2700K, 4000K, 5000K & 6500K on request
IP Rating	IP66	IP65
Integrated lensing options	60° narrow, 90° medium, 110° wide	110° - wide beam
Lensing selection guidelines - Warehousing aisle width	60°: aisle width 1-2m 90°: aisle width 2-3m 110°: aisle width 4-5m, loading docks & warehouse	General storage Loading docks Warehouse
smartsense IP65 controls -optional	2 & 3 step dimming microwave motion sensing daylight sensing	2 & 3 step dimming microwave motion sensing daylight sensing DALI enabled driver
Mounting	Hanging or direct mount	Easy hook hanging
Mounting accessories - standard	Stainless steel hanging kit 3m flex & plug included	2m flex & plug included
Mounting accessories - optional	Adjustable mounting bracket	Adjustable mounting bracket