





Standard / Emergency T8 & T5 Fluorescent battens

Existing luminaire	 Chamaeleon III	 Chamaeleon Eco	 Chamaeleon Deco	 Vico batten				
2 x 14W T5 (2ft)	42/4W 3500 lm	22/3W 2500 lm	21/9W 1800 lm	18/5W 2175 lm				
2 x 18W T8 (2ft)								
1 x 28W T5 (4ft)						36/8W 4020 lm		
1 x 36W T8 (4ft)								
2 x 28W T5 (4ft)								
2 x 36W T8 (4ft)								
2 x 58W T8 (5ft)							44/10W 4780 lm	

Metal halide / Mercury vapour / High pressure sodium

Existing luminaire	 Stargate highbay	 Tauro Eco highbay	 Supernova floodlight	 Cincinnati under canopy	 Zorro area/street	 Lake downlight
35W						22W 2320 lm
70W					35W 3900 lm	32W 3390 lm
150W	100W 12500 lm	80W 9050 lm			35W 3900 lm 65W 7330 lm	
250W	100W 12500 lm 150W 18750 lm	80W 9050 lm 120W 13540 lm			65W 7330 lm 100W 11230 lm 135W 15050 lm	
400W	100W 12500 lm 150W 18750 lm 200W 25000 lm	120W 13540 lm 160W 17550 lm 200W 22650 lm 240W 26990 lm	120W 13540 lm 160W 17550 lm 240W 26990 lm	120W 13540 lm 160W 17550 lm	2 x 65W 14660 lm 100W 11230 lm 135W 15050 lm 165W 18400 lm 200W 22220 lm	

Compact Fluorescent & T8/T9 Circular Fluorescent

Existing luminaire	 Lake downlight	 Chamaeleon Deco	Existing luminaire	 Lake downlight	 Chamaeleon Deco
1 x 18W CFL	12W 1290 lm		1 x 32W T8/T9		21W 1800 lm
1 x 22W CFL			1 x 40W T8/T9		
1 x 22W T8/T9		21W 1800 lm	3 x 13W CFL		
1 x 26W CFL	12W 1290 lm		2 x 26W CFL	32W 3390 lm	
2 x 13W CFL			2 x 32W CFL		
1 x 32W CFL	22W 2320 lm		2 x 36W CFL		
2 x 18W CFL		21W 1800 lm			
2 x 22W CFL					

Note: This table is to be used as a guide only. Enlighten recommends a photometric performance comparison and/or a lighting design to ensure AS 1680 compliance is met.